



# PREMIUM™

## INTERIOR EGGSHELL 1203XX

### Interior Wall & Ceiling Paint

Our classic, high quality acrylic paint has been tested and is trusted by the people of the Northwest. It has become the paint of choice for everyday projects by homeowners and professionals alike. Premium™ is specially formulated to provide rich, lasting color and performs well in today's popular deep-toned colors. Available in four sheens, it is perfect for any wall surface in your home or office.

#### PRODUCT INFORMATION

<b>Resin:</b>	Vinyl Acrylic	<b>Weight Per Gallon:</b>	10.9 lbs
<b>Color Range:</b>	Whites and Custom Tints	<b>Solids by Weight:</b>	48.6% ± 2%
<b>Finish:</b>	4-10 @ 60° 8-20 @ 85° Gloss Level 2	<b>Solids by Volume:</b>	34.7% ± 2%
<b>Drying Time:</b>	To Touch: 1 Hour	<b>Recommended Film Thickness:</b>	Wet: 4.5 mils Dry: 1.5 mils
<b>(70° F &amp; 50% R.H.)</b>	To Recoat: 4 Hours	<b>Practical Coverage:</b>	350 - 400 FT <sup>2</sup> Per Gallon
<b>Clean Up:</b>	Soap & Water	<b>VOC:</b>	<50 g/L*
<b>Sizes:</b>	Quarts, Gallons, Fives	<small>*Maximum VOC content for non-tinted paint base is less than 50 g/L (40 CFR 59.406). VOC content may increase after tinting product.</small>	
<b>Tint Bases:</b>	White 120310    Deep 120325    Neutral 120340		

#### REGULATORY COMPLIANCE

Architectural and Industrial Maintenance Coating (AIM - EPA)  
South Coast Air Quality Management District (SCAQMD)  
California Air Resources Board (CARB)

Greenseal GS-11 Standard  
LEED v4 CDPH v1.2 Standard VOC Emissions Compliant  
MPI #44

#### SURFACE PREPARATION

**General:**  
All surfaces must be firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. De-gloss shiny surfaces by lightly sanding†. Repair cracks and fill voids.

†See warning for existing lead-based paint under Precautions.

#### New Surfaces:

Follow general surface preparation guidelines. New concrete or stucco must cure for 30 days prior to coating. Moisture content should be less than 12 % as measured with a moisture meter and the pH should be between 7 and 11. Remove all laitance and efflorescence before priming with the appropriate primer.

#### Previously Painted Surfaces:

Follow general surface preparation guidelines. Remove loose or failing paint and spot prime bare areas or entire surface with the appropriate primer. Hard, glossy surfaces may require sanding and/or a bonding primer.

**Spraying and Backrolling recommended on new flat work. To avoid lap marks, maintain a wet edge. Keep product from freezing. Do not apply when material, air, and/or surface temperature is below 45°F.**

#### RECOMMENDED PRIMERS

<b>Concrete, Stucco, and Masonry:</b>	Ph Surfacer Int/Ext Alkali Resistant Primer 620011 Super Seal HB Primer 225011
<b>Concrete Block:</b>	Block Filler 481011
<b>Wood:</b>	All Purpose Int/Ext Stain Blocking Primer 470011 Trim/Cabinet Undercoater 270011
<b>Ferrous Metal, Galvanized Metal, or Aluminum:</b>	Acrimetal DTM Low Sheen Primer/Finish 310210 All Purpose Int/Ext Stain Blocking Primer 470011
<b>Gypsum Wallboard:</b>	Premium PVA Interior Primer 220011 Super Seal HB Interior Primer 225011 Acro Pure Interior Primer 210011 Acrylitex MPI #50 Primer 296017 Qwik Prep Plus HB Interior Primer 235011

**OTHER PRIMERS MAY BE APPROPRIATE. CONTACT MILLER PAINT FOR MORE INFORMATION.**

#### APPLICATION

**Brush:** Nylon/Polyester Brush  
**Roller:** 3/8" - 3/4" Nap Synthetic Cover  
**Airless Spray:** .017" - .021" Tip Size

#### THINNING

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon. Stir product thoroughly.

#### PRECAUTIONS

**WARNING!** If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information, consult the Material Safety Data Sheet for this product.

**USE ONLY WITH ADEQUATE VENTILATION**

**KEEP OUT OF REACH OF CHILDREN**

#### WARRANTY

Miller Paint warrants satisfactory results of our products if used according to label directions. If not satisfied, return the unused portion to place of purchase with a sales receipt. Material will be replaced or purchase price will be refunded. Since we have no control over surface preparation or application, THIS WARRANTY DOES NOT INCLUDE LABOR, THE COST OF LABOR OR INCIDENTAL OR CONSEQUENTIAL DAMAGES ASSOCIATED WITH USE OF THIS PRODUCT. Some states do not allow the exclusion of incidental or consequential damages, so the limitation or exclusion contained in the above warranty may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

#### DISPOSAL

Never pour leftover coating down any sink or drain – use up material on the job or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal or recycle guidelines, contact your local waste management agency or district. Please re-use or recycle.