



# Acrinamel®

MULTIPURPOSE ACRYLIC ENAMEL



A multi-purpose acrylic enamel ideal for both exterior and interior projects, Acrinamel® provides an exceptionally durable finish for surfaces that require a moisture-resistant, washable coating. Ideal for exterior hardwood or pressure-treated wood, as well as interior wood, masonry, and metal surfaces. Its durable, moisture-resistant film provides the performance of an enamel finish with the benefits of water clean-up and low odor.

- **High quality 100% acrylic enamel**
- **Excellent color and sheen retention**
- **Excellent resistance to moisture**
- **Soap and water clean up**

## EGGSHELL

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. Also applicable for commercial or residential projects that require minimal washability such as conference rooms, living rooms, or bedrooms.

## SATIN

This finish will minimize dirt pick-up and is washable. With the hard finish of an enamel, a satin finish can also be used on interior walls where a strong, durable moisture resistant surface is needed. Best used when the surface is free of major imperfections. Use in applications such as interior primed smooth or rough walls, exterior or interior finish grade wood trim, or primed metal surfaces.

## SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease, and moisture. Use in applications such as institutional walls, trim, and wet areas, exterior or interior doors, exterior or interior finish grade wood trim, or primed metal surfaces.



## SPECIFICATIONS FOR ACRINAMEL®

	EGGSHELL	SATIN	SEMIGLOSS
VOLUME SOLIDS	35.9%	36.5%	36%
VISCOSITY	100-105 KU	100-105 KU	103-108 KU
WEIGHT PER GALLON	11.01 (LB)	10.67 (LB)	10.39 (LB)
GLOSS	4-10%@60° 8-20%@85°	10-20%@60° 30-40%@85°	35-55%@60° 60-70%@85°
V.O.C. (MINUS WATER)	49 G/L	48.9 G/L	47.5 G/L



**COVERAGE:** Approximately 350-400 square feet per gallon @1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

**DRY TIME:** One hour to touch and four hours to recoat @70°F and 50% relative humidity.

## ABOUT MILLER PAINT

Manufactured in Portland, Oregon since 1890, Miller Paint is an employee-owned company with over 50 stores throughout Oregon, Washington and Idaho. Miller Paint products are specifically formulated for the Pacific Northwest climate and are known for outstanding quality and durability. Praised for exceptional customer service and color expertise, Miller Paint is the region's go-to paint for homeowners and professionals alike.

**For a location near you, go to [www.millerpaint.com](http://www.millerpaint.com)**

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16