



Acro Pure

ENVIRONMENTALLY RESPONSIBLE



Acro Pure line of paints are low odor, ultra-low VOC*, and certified Indoor Advantage Gold for indoor air quality. Acro Pure paints are 100% acrylic, providing excellent coverage and durability for interior residential and commercial spaces. An environmentally-responsible paint, Acro Pure is the perfect choice for homes, schools, and healthcare environments.

- **Ultra-Low VOC***
- **Low odor**
- **100% Acrylic**
- **Great Coverage and Hide**
- **Excellent Splatter and Stain Resistance**
- **Superior Washability and Easy Clean Up**

*Maximum VOC content for this product is less than 6 g/L as determined by ASTM Test Method D 6886 and compliant with CDPH V1.2 Standard Emissions. Tinting may increase VOC content.

FLAT

A flat finish will minimize visibility of surface imperfections due to lack of light refraction. It is less washable and therefore ideal for theater/performing arts and residential or commercial projects where no sheen is desired and minimal traffic will be expected. Ideal for ceilings and walls with uneven surfaces.

EGGSHELL

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed. Also applicable for commercial or residential projects that require minimal washability such as conference rooms, living rooms, or bedrooms.

SATIN

This finish will minimize dirt pick-up and is washable. Ideal for projects where a deep, rich look and some sheen is desired, such as offices, hotel rooms, bedrooms, or hallways.

SEMIGLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Ideal for projects in high traffic areas such as waiting rooms, restaurants, and other public areas.



SPECIFICATIONS FOR ACRO PURE WALL FINISH

	FLAT	EGGSHELL	SATIN	SEMIGLOSS
VOLUME SOLIDS	39.25%	34.7%	36.2%	34.2%
VISCOSITY	98-103 KU	98-103 KU	98-103 KU	98-103 KU
WEIGHT PER GALLON	11.73 (LB)	11.12 (LB)	10.7 (LB)	10.3 (LB)
GLOSS	<5% @60°	5-10% @60°	10-20% @60°	45-55% @60°
V.O.C. (MINUS WATER)	<6 G/L	<6 G/L	<6 G/L	<6 G/L



COVERAGE: Approximately 300-400 square feet per gallon @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface.

DRY TIME: One hour to touch and four hours to recoat @ 70°F and 50% relative humidity.

ABOUT MILLER PAINT

Manufactured in Portland, Oregon since 1890, Miller Paint is an employee-owned company with over 50 stores throughout Oregon, Washington and Idaho. Miller Paint products are specifically formulated for the Pacific Northwest climate and are known for outstanding quality and durability. Praised for exceptional customer service and color expertise, Miller Paint is the region's go-to paint for homeowners and professionals alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16