



# MILLER PAINT

## SAFETY DATA SHEET (SDS)

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### PROUDCT IDENTIFICATION:

**Product Name:** ACRILITE SEMIGLOSS  
**Product Number:** 510-5-40 NEUTRAL BASE  
**Product Use:** Water-thinned Paint

#### MANUFACTURER:

Miller Paint Company, Inc.  
12812 NE Whitaker Way  
Portland, Oregon 97230  
www.millerpaint.com

**Manufacturer's Phone:** 503.255.0190  
**Emergency (24-hour) Phone:** 800.424.9300

**Date of preparation:** December 1, 2020

**Date of previous issue:** December 5, 2016

### 2. HAZARDS IDENTIFICATION

**Hazard Statement:** This mixture does not meet the criteria for classification.

**Primary Routes of Exposure:** Eye contact, Skin contact, Inhalation, Ingestion

#### Potential Acute Exposure Effects:

**Eyes:** May cause slight irritation  
**Skin:** May cause mild irritation  
**Inhalation:** May cause irritation of respiratory tract  
**Ingestion:** May be harmful if swallowed

#### Overexposure signs/symptoms:

**Eyes:** Watering, redness or irritation  
**Skin:** Irritation, dryness  
**Inhalation:** Respiratory tract irritation, coughing  
**Ingestion:** No specific data

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

<u>REPORTABLE COMPONENTS</u>	<u>CAS NUMBER</u>	<u>% by WEIGHT</u>
none		

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### 4. FIRST AID MEASURES

**Eyes:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.  
**Skin:** Remove contaminated clothing. Wash thoroughly with soap and water.  
**Inhalation:** Move to fresh air. Seek medical attention if symptoms continue.  
**Ingestion:** Do not induce vomiting. Get medical attention immediately.

## 5. FIRE FIGHTING MEASURES

**Flammable Properties:** This product is not flammable  
**Extinguishing Media:** Use foam, carbon dioxide, dry powder, water fog, or an extinguishing agent appropriate for the surrounding fire.  
**Unusual Fire and Explosion Hazards:** Closed containers may rupture or explode when exposed to extreme heat (due to build-up of pressure). During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.  
**Protective Equipment:** Firefighters should wear self-contained breathing apparatus and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Prevent further leakage or spillage. Soak up with inert absorbent material and transfer to a suitable container for proper disposal.

## 7. HANDLING AND STORAGE

**Handling:** Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray mists or sanding dust. Provide adequate ventilation. Wear appropriate respiratory equipment if ventilation is inadequate. Wash thoroughly after handling.  
**Storage:** Keep container closed when not in use. Transfer only to properly labeled containers. Keep out of reach of children.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Measures:** Use only in well ventilated areas. Ensure adequate ventilation, especially in confined areas.  
**Personal Protective Equipment:**  
**Eye / Face Protection:** Wear safety glasses or goggles.  
**Skin Protection:** Protective gloves and impervious clothing  
**Respiratory Protection:** If exposure cannot be controlled below acceptable limits by ventilation, use an appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all manufacturers' instructions.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Liquid  
**Color:** Various  
**Odor:** Little or no odor  
**Vapor pressure:** Not available  
**Odor threshold:** Not available  
**Vapor density:** Not available  
**pH:** 8 to 10  
**Density:** 8.8 (lbs / gal)  
**Viscosity:** 110 - 115 KU  
**Melting/freezing point:** Not available  
**Solubility (water):** Not available  
**Boiling point / range:** Not available  
**Flash point:** Not available  
**Evaporation rate:** < 1 (butyl acetate = 1.0)  
**Upper flammability limit:** Not available  
**Lower flammability limit:** Not available

**Auto-ignition temperature:** Not available  
**Decomposition temperature:** Not available

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.  
**Conditions to avoid:** None known.  
**Materials to avoid:** Strong oxidizing agents and strong acids.  
**Hazardous Decomposition Products:** None under normal use.  
**Hazardous Polymerization:** None under normal conditions.

## 11. TOXICOLOGICAL INFORMATION

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Disposal Instructions:** Do not allow material to drain into sewers/water supplies. Dispose of in accordance with all federal, state and local regulations. Consider recycling.

## 14. TRANSPORT INFORMATION CONSIDERATIONS

Not regulated

## 15. REGULATORY INFORMATION

**TSCA:** All materials are listed or exempt.

**California Proposition 65:** This product may contain small amounts of material known to the state of California to cause cancer or reproductive harm.

## 16. OTHER INFORMATION

### Hazardous Material Identification System (USA)

<b>Health:</b>	<b>1*</b>	(chronic hazard)
<b>Flammability:</b>	<b>0</b>	
<b>Physical Hazard:</b>	<b>0</b>	

**Prepared by:** Miller Paint Technical & Compliance Department

The information contained herein is presented in good faith and is believed to be accurate as of the date prepared. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information available to them.