



Acriclear

WATER BASE INTERIOR



Acriclear is a crystal clear, water-based, non-yellowing blend of polyurethane and acrylic resins. It is specifically formulated for interior wood applications such as furniture, wood work, and craft items. This product has exceptional scratch resistance and is low odor. This product is not recommended for exterior wood surfaces, floors, or non-wood surfaces.

- **Dries Crystal Clear**
- **Exceptional Scratch Resistance**
- **Low Odor/Easy Clean Up**

MATTE

A flat finish will minimize visibility of surface imperfections due to a lack of light refraction. It is less washable and designed for applications where to sheen is desired, such as ceilings, formal living and dining rooms or uneven surfaces.

SATIN

Ideal for projects where a deep, rich look is desired yet only a minimal sheen is needed, and mostly seen at an angle. It reduces dirt pick-up and provides some washability. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections.

SEMIGLOSS

This finish will minimize dirt pick-up and is washable. Ideal for full body exterior work where some sheen is desired. Best used when the surface is free of major imperfections. Use in applications like exterior body, sidings (wood or metal), exterior rough or smooth trim.

GLOSS

This high-sheen product is very washable and perfect for areas that are more susceptible to dirt, grease and moisture. Use in applications like exterior smooth siding, exterior smooth wood trim, and primed metal surfaces.



SPECIFICATIONS FOR ACRICLEAR INTERIOR

	MATTE	SATIN	SEMIGLOSS	GLOSS
VOLUME SOLIDS	26	42.5%	39.0%	39.0%
VISCOSITY	58-65 KU	58-65 KU	58-65 KU	58-65 KU
WEIGHT PER GALLON	8.7 (LB)	8.6 (LB)	8.5 (LB)	8.5 (LB)
GLOSS	10-20% @ 60°	35-45% @ 60°	60-70% @ 60°	75-85 @ 60°
V.O.C. (MINUS WATER)	<250	<250	<250	<250



COVERAGE: Approximately 300-400 square feet per gallon. @ 1.5 dry mils. Two coats recommended for even coverage. Coverage depends on porosity and profile of the surface. Properly prepared surfaces provide the best coverage.

DRY TIME: One hour to touch and two-three hours to recoat @ 70°F and 50% relative humidity.

ABOUT MILLER PAINT

Manufactured in Portland, Oregon since 1890, Miller Paint is an employee-owned company with over 50 stores throughout Oregon, Washington and Idaho. Miller Paint products are specifically formulated for the Pacific Northwest climate and are known for outstanding quality and durability. Praised for exceptional customer service and color expertise, Miller Paint is the region's go-to paint for homeowners and professionals alike.

For a location near you, go to www.millerpaint.com

Specification figures should be taken as accurate for products being produced at the time of publication in untinted white bases only. Formulation improvements may be made from time to time that may affect these figures to some degree. Manufacturing tolerances of +/-2% are considered acceptable. Whenever a change is made that the Manufacturer considers substantial, the specification will be revised. Miller and Miller Paints are registered trademarks of Miller Paint Co., Inc. Portland, OR. REV 9/16